Operating the Network Service Header (NSH) with Next Protocol "None"

draft-farrel-sfc-convent-02.txt
Adrian Farrel <afarrel@juniper.net>
John Drake <jdrake@juniper.net>
[Lucy Yong – retired]

IETF-99, Prague, July 2017

Sending Metadata without User Data

- Metadata is carried in the NSH
- The NSH is designed to be inserted between the forwarding header and the payload packet
- Thus metadata can be sent whenever there is a user data packet
- But what if...
 - There is no user data packet in hand?
 - The metadata is too large to include in the packet?

The Next Protocol Field

 NSH field used to identify the payload packet draft-ietf-sfc-nsh-13 defines...

0x1: IPv4

0x2: IPv6

0x3: Ethernet

0x4: NSH (for recursive NSH)

0x5: MPLS

- Propose to use 0x0: None
 - There is an NSH
 - There is no user data following the NSH
- Can send metadata without a user data packet

Use Cases

- Per-SFC and per-flow metadata
 - Send it when you're ready to send it
 - Compare with out-of-band installation of metadata
- Communication channel between SFIs
 - For coordination
 - As a control or management plane channel
- And if I suggest OAM, all hell will break loose
- Non-use case...
 - Per-packet metadata
 - Unless you are choosing from a set of pre-installed metadata

Processing Rules – Unknown Next Protocol

Legacy SFC-aware nodes that are unaware of the meaning of the "Next Protocol" value "None" will act as follows:

- SFFs will forward the packets
 - They look like any other NSH packet
- SFC Proxies will drop the packets
 - They know their SFs do not support this payload type
- SFIs will most likely drop the packets
 - They *could* be configured to take no action and return the packet to the SFF, but this is "unwise"
- Reclassifiers will most likely drop the packets
 - Classification is about processing the payload

Discuss!